


511

OEM

Pressure transmitter
Relative -1 ... 600 bar
Absolute 0 ... 25 bar



EDITION 03/2004

HUBA-REGISTERED TRADE MARK

 **Huba Control**

FOR FINE PRESSURE AND FLOW MEASUREMENT




EDITION 03/2004

Technical overview

These compact OEM pressure transmitters type series 511 meet the highest specification for mechanical stress, EMC compatibility, and operational reliability, which means that this range is particularly suitable for all demanding industrial applications.

This sensor utilises a ceramic technology, developed by Huba Control and for the last 10 years, in millions of applications, used in combination with unique integrated electronic design, means that the type 511 series has a high degree of accuracy for all temperature ranges. These units are available in small or production quantities, with an excellent price to performance ratio.



Legend to cross-section drawing

- 1 Connection fitting
- 2 Protection of media leakage
- 3 Sealing
- 4 Ceramic cell
- 5 Electronic with EMC-protection
- 6 Electrical connection (example Quickon)

Pressure ranges

Absolute pressure
Relative pressure (Gage)
(differential measurement of pressure relative to ambient pressure).

Overload

3.0x Full scale at -1 ... 4 bar
2.5x Full scale at 6 ... 600 bar
but as a maximum 900 bar
Higher overload on request

Rupture pressure

3.0x Full scale at -1 ... 4 bar
2.5x Full scale at 6 ... 600 bar
but as a maximum 900 bar
Higher rupture pressure on request
Patented media stop system to prevent media egress when exceeding rupture pressure range (≥ 40 bar nominal value)

Accuracy

Total of linearity, hysteresis and repeatability
Adjustment bar Adjustment psi
< +/- 0.3% fs < +/- 0.5% fs
Adjustment accuracy zero point and full scale
Adjustment bar Adjustment psi
< +/- 0.3% fs < +/- 0.5% fs

Housing material

Casing:
Stainless steel 1.4305 (AISI 303)

Materials in contact with the medium

Ceramic Al₂O₃/
Stainless steel 1.4305 (AISI 303)
Media stopper: PPS
Sealing material: optionally FPM, NBR, others on request

The distinct advantages

- Compact, rugged construction for highest operational reliability
- Protection IP 67 standard
- No media egress when exceeding rupture pressure (patented)
- Negligible temperature influence on accuracy
- Excellent EMC-capacity
- Saving time by quick cable mounting by the customer with Quickon-System

Application temperature

Medium temperature with sealing:
FPM -15 ... +125 °C
NBR -25 ... +85 °C
FPM spec. -40 ... +150 °C
Ambient temperature:
For all versions max. 85 °C
For versions with connector AMP and ratiometric output max. 125 °C
(Versions up to 150 °C on request)

Temperature influences

	Adjustment bar	Adjustment psi
TK0	< ± 0.015% fs/K	< ± 0.025% fs/K
TKE	< ± 0.015% fs/K	< ± 0.015% fs/K

temperature range -40 ... +125 °C

Dynamic response

Suitable for static and dynamic measurements.
Response time < 2 ms
typ. 1 ms

Pressure connections

See order code selection table

Weight

Version inside thread 85 grams
Version outside thread 95 grams

Installation arrangement

Unrestricted

Signal/Power supply

See order code selection table
• Short circuit-proof and protected against polarity reversal. Each connection against other with max. +/- supply voltage.
Electric strength 500 VDC, on request 1000 VDC

Load

Voltage outputs:
> 10 kOhm / < 100 nF
Output
4 - 20 mA $\leq \frac{\text{supply voltage} - 8 \text{ V}}{0.02 \text{ A}}$ [Ohm]
Ratiometric
>10 kOhm/< 100 nF

Current consumption

With max. signal output
Voltage outputs: < 4 mA
4 - 20 mA < 20 mA
Ratiometric < 4 mA

Electrical connections / Protection standard

See order code selection table

Tests / Admissions

Shock acc. IEC 68-2-27, 75 G, 11 ms half sine wave, all 3 directions.
Free fall from 1 m on concrete (6x).
Constant shock acc. IEC 68-2-29 40 G for 6 ms, 1000x all 3 directions.
Vibration acc. IEC 68-2-6, 20 G, 9 ... 200 Hz, 2 ... 9 Hz with amplitude +/- 15 mm, 1 Octave / min. all 3 directions, 50 constant load.
EMC-behaviour see on the back.
UL according to standard 60730

Versions




		X	X	X	X	X	X	X	X	X	X
Relative pressure		9									
Absolute pressure		8									
Pressure ranges in bar ¹	-1 ... + 0 bar	9	0	0							
	0 ... + 1 bar		1	1							
	0 ... + 1.6 bar		1	2							
	0 ... + 2.5 bar		1	4							
	0 ... + 4 bar		1	5							
	0 ... + 6 bar		1	7							
	0 ... + 10 bar		3	0							
	0 ... + 16 bar		3	1							
	0 ... + 25 bar		3	2							
	0 ... + 40 bar	9	3	3							
	0 ... + 60 bar	9	4	0							
	0 ... + 100 bar	9	4	1							
	0 ... + 160 bar	9	4	2							
	0 ... + 250 bar	9	4	3							
	0 ... + 400 bar Viton seal only	9	5	4	6						
	0 ... + 600 bar Viton seal only	9	5	5	6						
Pressure ranges in psi ¹	-30 ... 0" hg		A	0							
	0 ... + 15 psi		B	1							
	0 ... + 30 psi		B	4							
	0 ... + 60 psi		B	5							
	0 ... + 100 psi		B	7							
	0 ... + 200 psi		C	1							
	0 ... + 300 psi		C	2							
	0 ... + 500 psi	9	C	3							
	0 ... + 750 psi	9	D	0							
	0 ... + 1000 psi	9	D	1							
	0 ... + 2000 psi	9	D	2							
	0 ... + 3000 psi	9	D	3							
	0 ... + 5000 psi Viton seal only	9	E	4	6						
	0 ... + 7500 psi Viton seal only	9	E	5	6						
	▲ Full scale signal at these pressures										
Sealing materials ²	FPM Fluoro-elastomer (Viton) - 15 ... + 125 °C				0						
	NBR butadiene-acrylic nitrile-caoutchouc - 25 ... + 85 °C				2						
	FPM Fluoro-elastomer (Viton) spec. - 40 ... + 150 °C				6						
Calibration	Factory calibrated in bar				0						
Outputs and power supply	0 - 5 V 8.0 - 33.0 VDC 3-wire cable							1			
	1 - 6 V 8.0 - 33.0 VDC 3-wire cable							6			
	0 - 10 V 11.4 - 33.0 VDC 3-wire cable							2			
	0 - 10 V 16 - 34 VDC/24 VAC +/- 15% 3-wire cable*							7			
	4 - 20 mA 8.0 - 33.0 VDC 2-wire cable							3			
	0.5 - 4.5 V, ratiometric 5 VDC (4.75 - 5.25) 3-wire cable							4			
	* Only with Quickon- and cable version										
Electrical connections	Cable, 1.5 meters IP 67 max. 85 °C								0		
	Quickon including cable screwing IP 67 max. 85 °C								1		
	Connector AMP (without female connector) IP 67 max. 125 °C								2		
	Connector M 12 x 1 (without female connector) IP 67 max. 85 °C								5		
Pressure connections ³	Inside thread G 1/4 with O-ring sealing									1	
	Outside thread G 1/4 sealed at back DIN 3852/E									4	
	Outside thread 1/4-18 NPT									3	
	Outside thread R 1/4, DIN 2999									7	
	Outside thread M 12 x 1.5									5	
	Outside thread M 14 x 1.5									6	
Process connections	Stainless steel without pressure tip orifice										1
	Stainless steel with pressure tip orifice (standard from ≥ 40 bar on)										2
	Stainless steel without pressure tip orifice, free of oil and grease (only seal Viton, not compound-filled, up to 160 bar)										3
	Stainless steel with pressure tip orifice (standard from ≥ 40 bar on) free of oil and grease (only seal Viton, not compound-filled, up to 160 bar)										4
Pressure range variation	Indicate W and mention range on order										W
Accessories	Female connector for connector M12 x 1 (not included in delivery)		1	0	6	9	7	5			
	Female connector AMP (Junior Power Timer) (not included in delivery)		1	0	8	7	6	7			
	Quickon cable screwing (included in delivery)		1	0	7	3	5	9			
Packaging	Mention on order: • single packaging / • multiple packaging (25 pcs) • Single packaging, accessories integrated • Multiple packaging (25 pcs), Quickon cable screwing enclosed										

¹ Other pressure ranges on request.

² According to ISO standard R 1629, other sealing materials on request.

³ Other pressure connections and materials on request.



Electromagnetic compatibility:
 CE conformity (EMC) by application of harmonized standards: Interference stability EN 50082-2, IEC 61000-6-2 and EN 61326-1, interference emit EN 50081-1, EN 55022, CISPR 22, EN 61326-1

Interference stability	Test standard	Effects
Electrostatic discharge (ESD)	EN 61000-4-2 15 kV air discharge, 8 kV contact discharge	No effect
High-frequency electromagnetic radiation (HF)	EN 61000-4-3 200 V/m, 80 ... 1000 Mz	No effect
Conducted HF interference	EN 61000-4-6 30 V, 0.15 ... 80 MHz	No effect
Fast transients (burst)	EN 61000-4-4 4 kV	No effect
Surge	EN 61000-4-5 Line-Line, Line-Case 500 V, 12 Ohm, 9 µF 1 kV, 42 Ohm, 0.5 µF Ratiometric Line-Line 500 V, 2 Ohm, 18 µF	No failure
Magnetic fields	EN 61000-4-8 30 A/m, 50 Hz	No effect
Insulation voltage	500 VDC (optional 1000 VDC) 350 VAC (optional 700 VAC)	No effect
Interference emit	Test standard	Effects
Conducted interference	EN 55022 0.15... 30 MHz	No emission
Radiation from housing	30...1000 MHz, 10 meters	No emission

Internet: www.hubacontrol.com

Huba Control Switzerland
 Headquarters
 Industriestrasse 17
 CH-5436 Würenlos
 Phone ++41 (0) 56 436 82 00
 Fax ++41 (0) 56 436 82 82
 e-mail: info.ch@hubacontrol.com

Huba Control United Kingdom
 Unit 3 Network Point
 Range Road
 GB-Witney Oxfordshire OX29 0YD
 Phone 01 993 776 667
 Fax 01 993 776 671
 e-mail: info.uk@hubacontrol.com

Huba Control France
 e-mail: info.fr@hubacontrol.com
Huba Control Germany
 e-mail: info.de@hubacontrol.com
Huba Control Netherlands
 e-mail: info.nl@hubacontrol.com

Agent for: